

UltraView LCD 42" Full HD Monitor, HDMI/VGA/BNC/DVI

UVM-4200

Specifications

Display	
Screen size:	42" TFT LCD
Aspect ratio:	16:9
Pixel pitch:	0.4845 x 0.4845mm
Viewing angle (H/V):	178° / 178°
Contrast ratio:	1500:1
Response time:	5ms (G-to-G)
Brightness:	500cd/m ² (max)
Recommended resolution:	1920 x 1080@60Hz
Video compatibility	NTSC/PAL Auto detect
Audio	
Speaker power:	5W x 2
Speakers:	Built-in
Interfaces	
BNC in/out (BNC):	2 / 2
S-Video in/out	1/1
Audio in (RCA):	2(stereo)
VGA in (15pin d-sub):	1
HDMI/DVI:	1/1
PC stereo in:	1
Head phone out:	1
Operations	
Controls:	Power, Up/Down, Left/Right, Source, OSD Menu
OSD:	English, French, Spanish, German, Italian, Polish
Remote control:	Yes
Power	
Consumption:	< 180W
Input voltage	100 ~ 240VAC
Filter type	3D Combfilter, Deinterlace
Dimensions	
W x H x D (without stand):	992 x 602 x 114(mm) / 39.06 x 23.70 x 4.49(inch)
W x H x D (with stand)	992 x 649 x 270(mm) / 39.06 x 25.55 x 10.63(inch)
W x H x D (box)	1095 x 765 x 343(mm) / 43.11 x 30.12 x 13.50(inch)
Weight	
Net (without stand)	29.5Kg (65.4lb)
Net (with stand)	31.7Kg (69.9lb)
Gross (box)	35.7Kg (79.7lb)
Panel lamp life	
	50,000 hours
Vesa wall mount holes	200 X 200, 400 X 200 mm
Accessories included	Power Cord, Manual
Housing material	Metal



- 42" TFT LCD
- 16:9 aspect ratio
- 1920 x 1080 recommended resolution
- 1,500:1 contrast ratio for crisp images
- 3D comb filter for optimal image quality
- Multiple inputs including BNC, VGA, HDMI, DVI
- 50,000 hours panel lamp life

Ordering Information

UVM-4200 UltraView LCD 42" Full HD Monitor, HDMI/VGA/BNC/DVI